

NAUTIZ X2 LF READER



P/N: NX2-1030

Backpack solution adding low frequency RFID capabilities to the Nautiz X2.

Size	35 mm x 66 mm x 40 mm Adds 18 mm (thickness) to the rear of the unit.
Weight	10g
Radio Frequency	125 / 134.2kHz (LF)
Housing	Material ABS UL94-V0, black
Power Supply	3.3V
Current Consumption	65mA (max.)
Read-/ Write Distance	Up to 30mm (depending on type of transponder)
Host Interface	Serial (logic level 3.3V) on "/dev/ttyMT3"
Transmission Speed	9600 baud (default), 115200 baud (max.)
Relative Humidity	5% to 95% non-condensing
Supported Transponders	125kHz / 134.2kHz: 4100, 4102, 4200 (only emulation of 4100,4102), 4050, 4150, 4450, 4550, AWID, CASI-RUSCO, Deister, HITAG 1 / 2 / S (without encryption mode), Keri, Miro, Pyramid, TIRIS/HDX, UNIQUE, FDX-B, Q5, TITAN, T55x7
Environment	
<i>Operating:</i>	-25°C to +80°C (-13°F to +176°F)
<i>Storage:</i>	-45°C to +85°C (-49°F to +185°F)

Handheld Group AB is a worldwide supplier of rugged PDAs and mobile computers. Together with partners Handheld deliver complete mobility solutions to businesses in industries such as logistics, forestry, geodesy, public transportation, construction, service & maintenance, military and security. The Handheld Group of Sweden has local offices in Sweden, Finland, the Netherlands, Italy, Germany, Switzerland, Australia, UK and the USA.

handheld
www.handheldgroup.com